

Technical Data

Solid state class D powered bass amplifier, 19" rack mountable, 2 rackspaces high.

Inputs

- 1 Jack 1/4" A for basses with normal output level, 3 MΩ
- 1 Jack 1/4" B for basses with higher output, additional pre-damping control, 4.7 MΩ

Equalization

- Bass + 15dB 60Hz, -15dB 30Hz
- Low +/- 12dB 130Hz
- Mid +/- 12dB 200Hz – 4KHz
- Treble +/- 15dB 8kHz

Outputs

- 1 Tune Send Jack 1/4"
- 1 Balanced DI Out XLR, pin 1 ground, pin 2 signal+, pin 3 signal -, adjustable level
- 2 Speakers Speakon, pin 1+ and 2+ signal hot, pin 1- and 2- signal cold
- 1 Phones Stereo-jack 1/4"

Effects

- 1 Parallel Loop, post eq, with mix feature (0-100%) and footswitch activation, also usable as MP3 input (stereo input 1/4" jack).

Switches

- 1 Input A/B (activates Input A or B)
- 1 Tune (cancels all outputs without Tune Send)
- 1 Eq On
- 1 Effect On
- 1 Power On
- 1 Ground Liff
- 1 DI pre/post Eq
- 1 Loop Return mono / MP3 In stereo
- 1 Footswitch jack Tune On
- 1 Footswitch jack Effect On

Special Features

- Class A input stage
- LED Overdrive Indicators for Pre-Amp and Power Amp
- LED Indicators for all switch functions
- Built in A/B box with separate damping control for Input B
- DI-Out adjustable (on left side by screwdriver)

- Output Power: 700 watts@4 Ω, 350 watts@8 Ω DIP-switches ON **or** 700 watts@2.7 Ω, 475 watts@4 Ω, 240 watts @ 8 Ω DIP-switches OFF
- Frequency Range: 20 Hz to 20 KHz -1dB
- Power Requirement: 200-260 V AC, 5A slo / 100-130V AC, 8A slo
- Dimensions: 320 x 88 x 260 mm (12.6 x 3.5 x 10.2")
- Weight: 5 kg (11 lbs)